## CRL BLUMCRAFT® BP100 SERIES PANIC HANDLES FOR BALANCED DOORS

- Specifically Designed for 1/2", 5/8" or 3/4" (12, 16 or 19 mm)
   Tempered Glass Balanced Doors
- . UL, ULC, and ANSI/BHMA Certified
- · Custom Finishes Available on Special Order
- Available in 304 Grade Polished and Brushed Stainless Steel, 385 Grade Satin and Polished Brass, and Oil Rubbed Bronze
- · Custom Sizes Ship in One to Two Weeks





**CRL-Blumcraft BP100 Series Panic Handles** are engineered to meet building code requirements for balanced doors while maintaining a streamlined visual.

According to code, the push pad cannot extend more than half the width of the balanced door, measured from the latch side. **BP100 Series Panic Handles** are unique in that they span the length of the balanced door. The first section, measured from the latch side, is a clearly defined push pad, while the second section extending towards the door hinge is a seamlessly integrated fixed handle. This wider handle offers improved aesthetics over a panic handle that only spans half the width of the balanced door.

For more information, contact the CRL Technical Sales team at **(800) 421-6144** ext. **17700** or email **architectural@crlaurence.com**.










 Exterior Handle Combinations for Balanced Doors With CRL Blumcraft® Panic Handles

## 60" (1524 mm) Maximum with 1/2" or 5/8" (12 or 16 mm) Glass **MAXIMUM DOOR HEIGHTS** 66" (1676 mm) Maximum with - 96" (2.44 m) for 1/2" or 5/8" 3/4" (19 mm) Glass (12 or 16 mm Glass Thickness Center of Keyed Access (203 mm) - 102" (2.59 m) for 3/4" (19 mm) Glass Thickness 10-1/2" - 102" (2.59 m) for 1/2" or 5/8" (12 or 16 mm) Glass Thickness (267 mm) - 108" (2.74 m) for 3/4" (19 mm) Glass Thickness Exception - When using "F" Style Exterior Handle - 108" (2.74 m) for either 1/2", 5/8" Center line or 3/4"(12, 16 or 19 mm) of Døor 4-1/8" Glass Thickness

CRL BALANCED DOOR PANIC HANDLE SIZE LIMITATIONS



**NOTE:** Exterior Fixed Handles shown above can be used in combination with our BP100 Series Panic Handle.

34" to 48" (864 to 1219 mm) Consult Local Building Codes

(105 mm)

Top Latching