



CRL LAMINATED TEMPERED GLASS RAILING PANELS

With CRL's Precise Edge Technology
• Superior Edge Quality for Open Edge Conditions
For "GRS" TAPER-LOC® Glass Rail Systems



Available Thickness:
9/16" (13.52 mm), 11/16" (17.52 mm), 27/32"
(21.52 mm), and 1-1/16" (25.52 mm) "Rail Glass"



- Laminated Clear Tempered and Low Iron Starphire® Glass Types Available for Use With CRL's GRS Laminated Glass Railing Systems
- Flat Polished Vertical Edges With CRL's "Precise Edge" Technology
- 48" and 60" (1219 and 1524 mm) Wide Glass Panels in Stock
- Custom Sizes, Fabrication, and Edge Work is Also Available
- Works With CRL's Patented Dry Glazed TAPER-LOC® System
- Also Designed for Use With CRL's New 30% Lighter 9BL Series Base Shoe
- Meets IBC 2015 Building Code Requirements

CRL's Laminated "Rail Glass" panels for glass balustrade applications meet the test criteria of ANSI Z97.1, and CPSC 16 CFR1201, and are produced with a rigid ionoplast interlayer. Our "Precise Edge" Technology dramatically improves the edge quality of laminated glass and gives each flat polished edge a consistent clean look and feel. All Laminated "Rail Glass" is available in two stock sizes. Custom sizes, fabrication, and edge work is also available upon request. **NOTE:** Boxing and crating charges will apply. Contact CRL's Railing Technical Sales for more information.

• Proudly Produced in the U.S.A

9/16" (13.52 MM) THICK LAMINATED TEMPERED GLASS

CAT. NO.	SIZE	DESCRIPTION
LG13C48	48" W x 41" H (1219 x 1041 mm)	Lami Clear Tempered
LG13C60	60" W x 41" H (1524 x 1041 mm)	Lami Clear Tempered
LG13CC	Custom Size (Specify)	Lami Clear Tempered
LG13LC	Custom Size (Specify)	Lami Low Iron Starphire® Tempered

Minimum order: 1 each. Boxing and crating charges will apply for all orders.
Glass Makeup: 1/4" (6 mm) x .060 (1.52 mm) Ionoplast x 1/4" (6 mm)
Thickness Range: 0.497" (12.62 mm) to 0.549" (13.94 mm)
Weight Per Square Foot (Pounds): 6.83

27/32" (21.52 MM) THICK LAMINATED TEMPERED GLASS

CAT. NO.	SIZE	DESCRIPTION
LG21C48	48" W x 41" H (1219 x 1041 mm)	Lami Clear Tempered
LG21C60	60" W x 41" H (1524 x 1041 mm)	Lami Clear Tempered
LG21CC	Custom Size (Specify)	Lami Clear Tempered
LG21LC	Custom Size (Specify)	Lami Low Iron Starphire® Tempered

Minimum order: 1 each. Boxing and crating charges will apply for all orders.
Glass Makeup: 3/8" (10 mm) x .060 (1.52 mm) Ionoplast x 3/8" (10 mm)
Thickness Range: 0.803" (20.40 mm) to 0.903" (22.94 mm)
Weight Per Square Foot (Pounds): 10.09

11/16" (17.52 MM) THICK LAMINATED TEMPERED GLASS

CAT. NO.	SIZE	DESCRIPTION
LG17CC	Custom Size (Specify)	Lami Clear Tempered
LG17LC	Custom Size (Specify)	Lami Low Iron Starphire® Tempered

Minimum order: 1 each. Boxing and crating charges will apply for all orders.
Glass Makeup: 5/16" (8 mm) x .060 (1.52 mm) Ionoplast x 5/16" (8 mm)
Thickness Range: 0.666" (16.92 mm) to 0.713" (18.12 mm)
Weight Per Square Foot (Pounds): 8.83

1-1/16" (25.52 MM) THICK LAMINATED TEMPERED GLASS

CAT. NO.	SIZE	DESCRIPTION
LG25CC	Custom Size (Specify)	Lami Clear Tempered
LG25LC	Custom Size (Specify)	Lami Low Iron Starphire® Tempered

Minimum order: 1 each. Boxing and crating charges will apply for all orders.
Glass Makeup: 1/2" (12 mm) x .060 (1.52 mm) Ionoplast x 1/2" (12 mm)
Thickness Range: 0.960" (24.90 mm) to 1.060" (26.92 mm)
Weight Per Square Foot (Pounds): 13.35



Starphire® is a registered trademark of PPG Industries Ohio, Inc.



C.R. LAURENCE COMPANY
Worldwide Manufacturer and Supplier
Glazing, Architectural, Railing, Construction, Industrial, and Automotive Supplies

Phone: (800) 421-6144 Ext. 7730
Fax: (866) 921-0532
Email: railings@crlaurence.com

crlaurence.com
usalum.com
crl-arch.com